



Declaration of Performance		
N° ABG310707LW		
Product Type:		HCB 7" LW
Intended use(s):		Masonry in non-load bearing building and civil applications in walls, columns and partitions that are designed not to be left exposed. These products are intended for use as a construction product in accordance with the applicable harmonised technical standards and specification as foreseen by the manufacturer.
Manufacturer:		Cementstone Manufacturing Company Ltd. C 7758 Attard Bros Group, "MikeSand", Industrial Zone, Ta' Qali, Malta ATD 4000
Authorised Representative:		Andrew Vella
System of AVCP:		System 2+
Harmonised Standard:		EN771-3:2011+A1:2015
Notified Body:		ABICert S.a.s. of Bianco Antonio & C. - NB 1982
Declared Performance		
Essential Characteristics		Performance
Configuration	Shape and Features	
	Group according to EN 1996-1-1 (EC6)	Group 2
Dimensions	Length	450 mm
	Width	173 mm
	Height	255 mm
	Tolerance Category	D1
Compressive Strength	Typical Mean Compressive Strength	2 N/mm <sup>2</sup>
	Direction of load	Perpendicular to bed faces
Bond Strength	Shear bond strength	NPD
	Flexural bond strength	NPD
Direct airborne sound insulation (in end conditions) / [Density and configuration]	Typical Gross Dry Density	650 kg/m <sup>3</sup>
	Configuration, dimensions and tolerances	See configuration
Water Absorption		Not to be left exposed
	Unit category	Category 1
Dimensional Stability		NPD
Water Vapour Permability		5/15 μ (Tabulated Value)
Typical Thermal Resistance / [Density and configuration] (for units intended to be used in elements subject to thermal insulation requirements)		0.622 m <sup>2</sup> K/W **
Durability against freeze / thaw		Not to be left exposed
Dangerous substances		NPD
Reaction to Fire		A1 (Commission Decision 2000/605/EC)
<p>The performance of the product identified above is in conformity with the set of declared performance/s. This de-claration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Furthermore the above declared performance and characteristics of the masonry unit as identified in this DoP, are achieved after 28 calendar days from production date.</p> <p><i>** Please refer to product's TDS for Thermal Conductivity value.</i></p> <p>Signed for and on behalf of the manufacturer by:</p> <p>Andrew Vella at Cementstone Manufacturing Company Ltd, Attard Bros Group, Ta' Qali</p> <p>on [date of issue] 06th September 2024</p> <p>[signature] </p>		



NB 1982

**Cementstone Manufacturing Company Ltd. C 7758**

Attard Bros Group, "MikeSand", Industrial Zone, Ta' Qali, Malta, ATD 4000

22

ABG310707LW

**EN 771-3:2011+A1:2015**

<b>Product:</b>	HCB 7" LW
<b>Intended use(s):</b>	Masonry in non-load bearing building and civil applications in walls, columns and partitions that are designed not to be left exposed. These products are intended for use as a construction product in accordance with the applicable harmonised technical standards and specification as foreseen by the manufacturer.
Characteristics	Performance
<b>Configuration:</b>	Group 2
<b>Dimensions:</b>	L: 450 mm    W: 173 mm    H: 255 mm
<b>Dimensional Tolerances:</b>	D1
<b>Typical Mean Compressive Strength:</b>	2.0 N/mm <sup>2</sup>
<b>Bond Strength:</b>	NPD
<b>Direction of load:</b>	Perpendicular to bed faces Category 1
<b>Typical Gross Dry Density</b>	650 kg/m <sup>3</sup>
<b>Water Absorption:</b>	Not to be left exposed
<b>Moisture Movement:</b>	NPD
<b>Water Vapour Permability:</b>	5/15 µ(tabulated value)
<b>Durability</b>	Not to be left exposed
<b>Reaction to Fire:</b>	A1

For other information visit our website: [www.attardbros.com](http://www.attardbros.com)

