


Declaration of Performance

N° ABG311311S

Unique identification code of the product-type:	Single Core 9"
Intended use(s):	Masonry in load bearing building and civil applications in walls, columns and partitions that are designed not to be left exposed. These products are intended for use as a construction product in accordance with the applicable harmonised technical standards and specification as foreseen by the manufacturer.
Manufacturer:	Cementstone Manufacturing Company Ltd. C 7758 Attard Bros Group, "MikeSand", Industrial Zone, Ta' Qali, Malta ATD 4000
Authorised Representative:	Andrew Vella
System of AVCP:	System 2+
Harmonised Standard:	EN771-3:2011+A1:2015
Notified Body:	ABICert S.a.s. of Bianco Antonio & C. - NB 1982

Declared Performance

Essential Characteristics		Performance
Configuration	Shape and Features	
	Group according to EN 1996-1-1 (EC6)	Group 2
Dimensions	Length	450 mm
	Width	220 mm
	Height	255 mm
	Tolerance Category	D1
Compressive Strength	Typical mean compressive strength	2 N/mm ²
	Direction of load	Perpendicular to bed faces
Bond Strength	Shear bond strength	0.15 N/mm ² (Fixed value)
	Flexural bond strength	NPD
Direct airborne sound insulation (in end conditions) / [Density and configuration]	Typical Gross Dry Density	1000 kg/m ³
	Configuration, dimensions and tolerances	See configuration
Water Absorption		Not to be left exposed
Unit category		Category 1

Dimensional Stability	NPD
Water Vapour Permability	5/15 μ (Tabulated Value)
Typical Thermal Resistance / [Density and configuration] (for units intended to be used in elements subject to thermal insulation requirements)	0.2377 m ² K/W **
Durability against freeze / thaw	Not to be left exposed
Dangerous substances	NPD
Reaction to Fire	A1 (Commission Decision 2000/605/EC)

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Furthermore the above declared performance and characteristics of the masonry unit as identified in this DoP, are achieved after 28 calendar days from production date.


*** Please refer to product's TDS for Thermal Conductivity value. The thermal conductivity/resistance is calculated based on the condition that the frogs are infilled with concrete having a density of 2200kg/m³*

Signed for and on behalf of the manufacturer by:

Andrew Vella at Cementstone Manufacturing Company Ltd, Attard Bros Group, Ta' Qali

on [date of issue] 06/09/2024

[signature]





NB 1982

Cementstone Manufacturing Company Ltd. C 7758

Attard Bros Group, "MikeSand", Industrial Zone, Ta' Qali, Malta, ATD 4000

24

ABG311311S

EN 771-3:2011+A1:2015

Product:

Single Core 9"

Intended use(s):

Masonry in load bearing building and civil applications in walls, columns and partitions that are designed not to be left exposed. These products are intended for use as a construction product in accordance with the applicable harmonised technical standards and specification as foreseen by the manufacturer.

Characteristics

Performance

Configuration:

Group 2

Dimensions:

L: 450 mm W: 220 mm H: 255 mm

Dimensional Tolerances:

D1

Characteristic Compressive Typical Strength:

2.0 N/mm²

Bond Strength:

0.15 N/mm² (fixed value)

Direction of load:

Perpendicular to bed faces Category 1

Typical Gross Dry Density

1000 kg/m³

Water Absorption:

Not to be left exposed

Moisture Movement:

NPD

Water Vapour Permability:

5/15 μ (tabulated value)

Durability

Not to be left exposed

Reaction to Fire:

A1

For other information visit our website: www.attardbros.com

